



| Copper Alloy UNS Number | ASTM Spec | Temper(s) | Product Description | Round Size Range | Hex/Oct Size Range |
|----------------------------|-----------|---------------|--|---------------------|-----------------------|
| C11000 | B152 | H04 | Electrolytic Tough Pitch Copper | 3/16" - 15" | N/A |
| C14500 | B301 | H02 | Tellurium Copper | 1/8" - 6" | 1/4" - 2" |
| C31400 | B140 | H02, H04 | Leaded Commercial Bronze | 3/8" - 2 1/2" | 3/8" - 2" |
| C31600 | B140 | H02, H04 | Leaded Commercial Bronze (Nickel-Bearing) | 3/8" - 2 1/2" | 3/8" - 2" |
| C36000 | B16 | H02, H04 | Free-Machining Brass | 3/32" - 16" | 5/32" - 4" |
| C46400 | B21 | H02 | Naval Brass | 3/16" - 12" | Up to 3" |
| C48500 | B21 | H01, H02 | Naval Brass "High Leaded" | 1/4" - 4" | N/A |
| C54400 | B139 | H04 | Phosphor Bronze B2 | 3/8" - 2 1/2" | 3/8" - 2" |
| C63000 | B150 | HR50 | Aluminum Bronze | 5/8" - 3" | 1/2" - 2" |
| C64200 | B150 | HR50 | Aluminum Bronze | 3/16" - 3" | 1/2" - 2" |
| C65500 | B98 | H02, H04, H06 | High Silicon Bronze "A" | 1/8" - 8" | 1/4" - 2" |
| C67300 | B249 | HR50 | Manganese Bronze | 1/4" - 4" | 4 1/4" - 16" |